OFFICE OF THE MARION COUNTY SURVEYOR	Raymona St. 2200 S
SECTION RECORD CORNER	ļu
SECTION 22 TOWNSHIP 15 RANGE 4	0
DATE: 6-10-02	2
PARTY CHIEF: Kiste	
CRFW:	A
TYPE OF MARKER: 5/8x48"rebar w/al.cap &	
METHOD OF ESTABLISHMENT: <u>County: magnet</u> NEW location	00.00
111 O D O E TOUE 1	8
NAME: 15042204 , 4	
N: 497740.2276(m) = 9	1
E: 64340.0288(m) / &	1 + 1 4
	/ / /
E: 64340.0288(m)	$f \not = f$
Ploo	1 1 1
4 - 1 0	1 ! 1
115'	
	T & 1
	/ / /
1 P	f i_1
2. 2. 25,	
2.	1/2/
1/3/	1. / 10/
1/0	1.
// \	00/15/
3.	1:1
o. o	[i]
al witness called for in Marion County Original field	notes were a 15" hand

Origin 18 links, 18" sugar maple S 54 W 8 links. 11—6—1849, Percy Hosbrook found the orignal witness stumps and set a new witness a 36" oak N 22 W 90 links per Center Township Legal Suvey Book pg. 38. 1—10—1850, Percy Hosbrook fd witnesses of original witness stumps and 36" oak N 22 W 90 links set rock per Warren Township Legal Survey Book pg. 24. 4-3-1850 D.B. Hosbrook fd witnesses per Warren Twp. 3-1-1864 P.W.Voorhis fd rock per Center Twp. 1922,. George Schmidt called a pin in pavement per Center Twp. Field Bk 16, pg. 61. Legal Survey 4-1941 called an iron pin per Warren Twp. pg. 86. MCSO tie card dated prior to 1-31-1952 called iron pin. MCSO tie card 1-31-1952 by Monroe called a 1/2" sq. brass plug. MSE Job 73-30 8-13-1973 called out bearings and distances for Sec. 21; however, does not call monument. Gene Darnall Job#77118, 9-6-19 called 5/8" steel rod w/al.cap. 3-5-79

capped rebar fd. Perpetuated corner by MCSO 1-20-99.

		10 20 20 20 20 20 20 20 20 20 20 20 20 20
REF.	DISTANCE	DESCRIPTION
1.	93.75	Cut ;x; NE bolt of light pole base
2.	7.22	Gene Darnall capped rebar
3.	34.91	Top center of R/W fence corner post
4.	15.5'	Northwesterly to edge of R/W fence line